

Cortina Grande®

Technical Data	Standards	Cortina Grande
Type of Floor Covering		Solid Vinyl Tile
Classification	ASTM F 1700	Meets Requirements
Total Thickness		1/8" (3.2 mm)
Static Load Limit	ASTM F 970†	800 psi (modified)
Tile Size		16" x 16" (40.6 cm x 40.6 cm)
Weight/sq. ft./m ²		1.22 lbs sq. ft. (13.08 lbs. m ²)
Carton Quantity		25 tiles = 44.44 sq. ft. (4.12 m ²)
Carton Weight		54 lbs (24.5 kg)
Flammability	ASTM E 648	Class 1 >0.45 CRF
Smoke Density	ASTM E 662	<450
Slip Resistance SCOF	ADA Compliant	Both smooth and slip resistant (SR)
Chemical Resistance		Good
Colors		50 smooth, 6 slip resistant
Warranty		10 Year LIMITED Warranty. See tarketna.com for complete warranty information.
Maintenance		2 coats of finish/Flexible maintenance depending upon use of the floor*

* Contact Tech Services for flexible maintenance options.

† Static load limit per ASTM 970 modified by specifying a higher load.

Please visit tarketna.com for the most updated specifications, and installation, cleaning and maintenance instructions.

The Johnsonite system includes transitions and finishing borders (wall base) to complete your flooring design and installation.

How to Order: Smooth: CG(XXX) Color Number Slip Resistant: CG(XXX) Color Number SR



16910 Munn Road
Chagrin Falls, OH 44023
800-899-8916 or 440-543-8916

tarketna.com



THE ULTIMATE FLOORING EXPERIENCE

©2013 Tarkett
Printed in the USA Revised 11/13

The contents of this document including, but not limited to, all text and images (Content) are owned by Johnsonite Inc. with all rights reserved unless otherwise noted. Any Content that is a trademark, logo, or service mark is also a registered and unregistered trademark of Johnsonite Inc. Your use of any Content without the written permission of Johnsonite Inc. is strictly prohibited.