



**Sports Strength's** vulcanized composition rubber molded tiles are engineered to provide support, durability, and superior noise and shock absorption. Sports Strength tiles are designed to withstand heavyweight impacts and are easy to install.



**FORCE REDUCTION 50.2%** 



**ENERGY RESTITUTION 47.9%** 

#### **Applications**

- Fitness
- Weight and Locker Rooms
- · Health and Fitness Centers
- Free Weights
- · Olympic-Style Lifting
- K-12/Higher Education

### **Product Features**

- Modular Tiles
- Easy Installation
- · Low-Maintenance
- Enhanced Impact
- Absorption for Moderate to Heavy Weight Drop Applications

#### **Installation Fast Facts**

- 15-Year limited warranty
- May be installed over most concrete, wood, or tile
- Floor must be level, in good condition and clear of dirt and loose debris.
- Dry laying and full inspection of all tiles will allow for a quality installation.

## **Physical Data**

Performance Criteria Density	Test Method	Results
Static Load Limit	ASTM F970	0.005" (@400psi)
Coefficient of Friction	ASTM D2047	>0.9
Abrasion Resistance	ASTM D3389	<1g, 1,000 cycles
Pill Test	ASTM D2859	Pass
Impact Insulation Class IIC*	ASM E492	56
Delta IIC*	ASTM E2179	27

\*Tested on a 6" concrete slab with no ceiling.


# **Product and Color Options**

• 24" x 24" tile, 1" thick (4 sq. ft.)




Proprietary Installation System **Quad Blok** 











To order, visit **LFishman.com** or contact your business rep for more information and availability.



6301 E. Lombard St., Baltimore, MD 21224 Toll-Free 1-800-556-7899 or customer\_care@LFishman.com

