

Leggett & Platt® Acoustical Underlayment

Whisper Step® Luxury Vinyl Underlayment


- For use under
- Luxury vinyl tile/plank
 - Rigid composite
 - Other premium resilient flooring



- High density for unmatched support under interlocking luxury vinyl flooring
- Provides significant reduction to impact noise in the room and floor below
- Can be used over most substrates – on, above, or below grade
- Installs quickly and easily
- Fresh Dimension® antimicrobial inhibits the growth of mold, mildew, and odor-causing bacteria
- Recommended by the Radiant Professionals Alliance for use over in-floor heating
- Hypoallergenic

SPECIFICATIONS

Composition:	Made of High-Density Synthetic Rubber	
Density:	62 lbs/ft ³ or 42 oz/yd ²	
Thickness:	0.056" (1.42 mm)	
R-Value:	0.02	
Moisture Barrier:	N/A*	
Color:	Green	
Castor Durability Test:	Passes 25,000 Cycles**	
Product Codes:	BM0042	BM0040
Dimensions:	36" x 33.33'	54" x 44.44'
Ft ² /Roll:	100	200
Yd ² /Roll:	11.11	22.22
Roll Weight:	29 lbs.	58 lbs.



Made of
**High-Density
Synthetic
Rubber**

For floating,
single, or
double-glue
installations

ACOUSTICAL PROPERTIES

Impact Insulation Class (IIC)***	66
ΔIIC	22
Sound Transmission Class (STC)***	63

PROTECTION

Indoor Air Quality:	CRI Green Label Plus-Certified
Antimicrobial:	Yes
Warranty:	Limited

* Separate moisture barrier should be used on slab foundation and below-grade installation

** Passes Castor Durability Test for 25,000 cycles when tested under minimum of 3 mm double-glued luxury vinyl plank and minimum 3.2 mm floating-click

*** When tested with floor-ceiling assembly

IIC: ASTM E492-09 / ASTM E989-06
 Δ IIC: ASTM E2179-03
 STC: ASTM E90 / ASTM E413-10



LPCarpetCushion.com



© 2016 Leggett & Platt Incorporated • MTLT2032_21152_12-16
 U.S.G.B.C. Member Logo is a trademark owned by the U.S. Green Building Council and is used by permission.
 FloorScore is a registered trademark of the Resilient Floor Covering Institute. SCS and/or certification marks are trademarks of Scientific Certification Systems.

Also for use under

- Laminate
- Engineered wood
- Hardwood