

Specification Sheet

NAFCO Vinyl and Rubber Cove Base

July 12, 2010

SPECIFICATIONS

	<u>.080" Vinyl Cove Base</u>	<u>1/8" Vinyl Cove Base</u>	<u>1/8" Rubber Cove Base</u>
Height:	4"	4" and 6"	4"
Length:	48" and 120' rolls	48" and 120' rolls	48" and 120' rolls
Weight per Carton:	33 lbs.	4" - 48 lbs. 6" - 70 lbs.	48 lbs.
ASTM F-1861:	Type TV, Group 2, Style B	Type TV, Group 2, Style B	Type TP, Group 2, Style B
ASTM E-84:	Class A	Class A	Class B

INSTALLATION

Use:	Residential and Commercial
Adhesive:	Tarkett 700. Available in gallon and 4 gallon containers. Note: .080" Vinyl Cove Base is available in Quick-Stik application for 48" pieces and 20' rolls.
Trowel Notch:	1/8" V-Notch.

- Maintain room temperature, cove base and adhesive at 70-75° F for 48 hours before, during and after installation. Maintain a minimum temperature of 55° F afterwards.
- Inside and outside corners are available.
- Cove base should be installed and rolled within 10 minutes of spreading the adhesive.
- The entire length of the piece to be installed must be pressed firmly to the wall to ensure a full transfer of adhesive.
- Hand roll cove base firmly in one direction, toward the last piece installed (opposite the direction in which the base is being installed).
- Refer to Tarkett (NAFCO) Installation Manual for complete and detailed instructions.

CARE AND MAINTENANCE

- Remove any excess adhesive from installation with soapy water. Use mineral spirits if adhesive dries.
- Damp wipe with a soft cloth to remove light dirt and dust.
- A mild detergent cleaner and water may be necessary to clean areas that become severely dirty.
- A soft cloth dampened with rubbing alcohol may be used to remove scuff marks.
- Avoid impacting wall base with heavy maintenance equipment (buffing machines).

LIMITED WARRANTY

- 1 Year Manufacturing Defects



THE ULTIMATE
FLOORING EXPERIENCE