

NovaCore™ Planks 6" x 48" (Clic: 5.74" x 47.74")



Boston (V3)

NNC-501



Rustic Jade (V2)

NNC-505



Williamsburg (V3)

NNC-502



Barnwood (V2)

NNC-506



Apple Caramel (V3)

NNC-503



Weathered Oak-Bungalow (V2)

NNC-507



Rustic Pine-Hazelnut (V2)

NNC-504



Weathered Oak-Cabin (V2)

NNC-508

NovaCore™ X-Large Planks 9" x 60" (Clic: 8.74" x 59.45")



Refined Walnut-Waverly (V4)

NNC-509



Refined Walnut-Ellis (V4)

NNC-510



European Oak-Lorimer (V2)

NNC-511



Refined Birch-Cognac (V1)

NNC-512



Old World Oak-Smoke (V2)

NNC-513



Old World Oak-Chocolate (V2)

NNC-514



Crescent Heart Pine-Honey (V3)

NNC-515



Crescent Heart Pine-Sandier (V3)

NNC-516

Specifications	HPC-Clic
Overall Thickness	5.0mm
Wear Layer Thickness	0.3mm (12 mil)
Plank Size	5.74" x 47.74"
X-Large Plank Size	8.74" x 59.45"
Urethane Protective Coating	Yes
Edge and Grout Effect	MBV
FloorScore®	Yes
Residential Warranty	Limited Lifetime
Light Commercial Warranty	10-Year
Plank Packaging	15 pcs. (28.55 sq. ft.)
X-Large Plank Packaging	8 pcs. (28.86 sq. ft.)
Plank Cartons/Pallet	50 pcs.
X-Large Plank Cartons/Pallet	64 pcs.
Plank Weight/Carton	31.26
X-Large Plank Weight/Carton	31.59

Specifications	HPC-Clic
ASTM F1700-13 Solid Vinyl Floor Tile	Class III, Type B
ASTM F137-08 Flexibility	Passes
ASTM F386-11 Thickness	Passes
ASTM F410 Wear Layer Thickness	Passes
ASTM F925 Stain and Chemical Resistance (5 minute & 24 hour)	Passes
ASTM F1514 Heat Stability	Passes
ASTM F1515 Light Stability	Passes
ASTM F1914 Immediate & Residual Indentation	Passes
ASTM F2055 Size and Squareness	Passes
ASTM F2199-09 Dimensional Stability	Passes
ASTM E648-06 Critical Radiant Flux	Class 1
ASTM E662 Smoke Density	Passes
ASTM F970-07 Static Load Limit	0.001" @ 250 psi
Static Load Limit (Modified)	>1,200 psi

