ACOUSTIC UNDERLAYMENT FOR LAMINATE, SOLID, AND ENGINEERED HARDWOOD

SILENT WALK™ SPECIFICATIONS

SPECIFICATION DATA

Product Code:	BV0185
Product Name:	Silent Walk™
Material Weight:	62 oz./sq. yd.
Density:	31 lbs./cu. ft.
Thickness:	0.156"
Product Dimensions:	54" x 40' (20 sy.)
Color:	Grey
Material Content:	Made with SBR Rubber
Design Configuration:	Flat/Flat
Approx. Shipping Wt.:	79 lbs. per roll
Antimicrobial:	Guardian™
Moisture Resistant:	98%
StainSTOP™:	Yes
Indoor Air Quality:	CRI Green Label Plus-Certified

FLAME CERTIFICATION

Pill Test:	Pass (DOC-FF 1-70)

THERMAL INSULATION

R-Value:	0.27

PRODUCT FEATURES

Designed for use under floating hardwood and laminate. Silent Walk™ can be installed on, above, or below grade. Acoustically engineered to reduce sound transmission and impact noise in the room and the floor below. Can be installed with or without the 4 mil poly film included in every roll.



ACOUSTICAL PERFORMANCE

IIC	IIC-72 w/floating laminate
STC	STC-65 w/floating laminate
RSD	Tested 4.5 dBa to 8.5 dBa quieter than standard foam paddings when tested as an assembly with laminate flooring. Measurements between 2000 Hz 4000 Hz utilizing ASTM E-492 tapping machine.

SCI® Sponge Cushion, Inc. A Leggett & Platt, Incorporated COMPANY

902 Armstrong Street | P.O. Box 709 | Morris, IL 60450 | 800.435.4062 | 815.942.2300 | FAX: 815.942.9636 | Sponge-Cushion.com | LPHospitality.com

U.S.G.B.C. Member Logo is a trademark owned by the U.S. Green Building Council and is used by permission.

©2016 Leggett & Platt, Incorporated | MTLT1148_20092_0516