

# SAFETY DATA SHEET (SDS)

## PRODUCT: ANCHOR HOT MELT CARPET SEAMING TAPE

### 1. Product and Company Identification

PRODUCT NAME: ANCHOR HOT MELT CARPET SEAMING TAPES:  
ANCHOR 10, 20, 40, 50 & GOLD LINE PLUS  
ANCHOR EZ MELT, EZ MELT II, Tri-State PROLOC III, & TK-20

MANUFACTURERS  
NAME: TRAXX CORPORATION

SYNONYMS: Heat Bond Seaming Tape

ADDRESS: 1201 E. LEXINGTON AVE.  
POMONA, CA 91766

CAS NUMBER: None

EMERGENCY  
TELEPHONE NO: 888-872-9926

DATE REVISED: September, 22, 2021

INFORMATION  
TELEPHONE NO: (909) 623-8032

PREPARED BY: C.K.PATEL

### 2. Hazard Identification

HMIS Rating:

Health: 0 Fire: 0 Reactivity: 0 PPE: B

This material is formulated with trade secret ingredients and does not contain any hazardous substances at or above OSHA and WHMIS reportable levels. Use this product as intended

### 3. Composition/Information on Ingredients

#### HAZARDOUS INGREDIENTS

None per OSHA Regulations: 29CFR1910.1200

None per SARA Title III, Section 313 and TCA 40 CRF 372

Hazardous Components: None

Non Hazardous Components: Resin, Polymers, Inert Ingredients

### 4. First-Aid Measures

#### EMERGENCY AND FIRST AID PROCEDURES:

INHALATION: If exposed to fumes from overheating/charring or combustion of adhesive, remove to fresh air.

EYES: Flush with large amount of cool water. Contact physician if irritation persists.

SKIN: If burned by contact with molten adhesive, cool as quickly as possible with water. Do not attempt to remove adhesive from skin. Burns should be treated as thermal burns. Obtain medical attention for burns.

INGESTION: Material is not likely to be ingested. Consult a physician if ingested.

### 5. Fire-Fighting Measures

#### FIRE AND EXPLOSION HAZARD DATA

FLASH POINT N/A AUTOIGNITION TEMPERATURE N/A

FLAMMABLE LIMITS IN AIR, % BY VOLUME N/A LOWER (LEL) N/A UPPER (UEL) N/A

EXTINGUISHING MEDIA Foam, Dry Chemical, CO<sub>2</sub>,

SPECIAL FIRE FIGHTING PROCEDURES None

UNUSUAL FIRE AND EXPLOSION HAZARDS None

## 6. Accidental Release Measures

**SPILL OR LEAK PROCEDURES**

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Not applicable for product in purchase form.

WASTE DISPOSAL METHOD: Dispose according to Federal, State and Local regulations.

## 7. Handling and Storage

**PRECAUTIONS FOR SAFE HANDLING AND USE**

PRECAUTION FOR HANDLING AND STORING: Keep out of reach of children. Avoid excessive heat and freezing.

OTHER PRECAUTIONS: Prevent or mitigate the generation of irritating vapors from overheating/charring of adhesive by insuring the iron is clean and operating at proper temperatures.

## 8. Exposure Controls and Personal Protection

**CONTROL MEASURES**

RESPIRATORY PROTECTION: Not required.

VENTILATION: Normal room ventilation with fans if necessary.

PROTECTIVE GLOVES: Not required.

EYE PROTECTION: Safety glasses recommended.

WORK/HYGIENE PRACTICES: General hygiene and safe handling procedures are believed to be generally applicable.

## 9. Physical and Chemical Properties

**PHYSICAL DATA**

APPEARANCE AND ODOR: Odorless, milky white/amber color solid adhesive covering a woven fabric scrim and paper.

BOILING POINT ((760 mm, Hg)	N/A	SPECIFIC GRAVITY (H <sub>2</sub> O=1)	0.98
-----------------------------	-----	---------------------------------------	------

VAPOR PRESSURE AT 20°C	N/A	VAPOR DENSITY (AIR=1)	N/A
------------------------	-----	-----------------------	-----

SOLUBILITY IN WATER:	Insoluble	PERCENT VOLATILES (BY VOLUME)	0
----------------------	-----------	-------------------------------	---

EVAPORATION RATE (BUTYL ACETATE = 1)	N/A	pH	N/A
--------------------------------------	-----	----	-----

VOLATILE ORGANIC COMPOUNDS (VOC)	Zero
----------------------------------	------

VOLATILE ORGANIC EMISSIONS (VOE)	None @ ambient temperature
----------------------------------	----------------------------

VOLATILE ORGANIC EMISSIONS (VOE)	Negligible @ application temperature <0.08 mg/m <sup>3</sup> (Cal/OSHA PEL 37 mg/m <sup>3</sup> )
----------------------------------	--

## 10. Stability and Reactivity

**REACTIVITY DATA**

STABILITY: Stable

CONDITIONS TO AVOID: Excessive Heat

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion Products

INCOMPATIBILITY:  
(MATERIALS TO AVOID) Strong Oxidizing Agents

HAZARDOUS POLYMERIZATION: Will Not Occur

## 11. Toxicological Information

### HEALTH HAZARD DATA

PRIMARY ROUTE OF ENTRY: N/A

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Overheating/charring may generate irritating vapors.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Molten adhesive will cause skin burns.

EFFECT OF OVEREXPOSURE: None Known

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None Known

HEALTH HAZARDS (Acute and Chronic): None

CARCINOGENICITY: This product contains No Carcinogens as listed by NTP, IRAC and OSHA

## 12. Ecological Information

### Toxicity

None Known

### Degradability

Not readily biodegradable.

### Other adverse effects

None Known

## 13. Disposal Consideration

### Product & Packaging Disposal

Dispose of according with the local/regional/state/federal/international regulations.

## 14. Transport Information

Not regulated per U.S.DOT, IATA or IMO

## 15. Regulatory Information

### U.S. Federal Regulation and State Regulations

Fire Hazard – No Pressure Hazard – No Reactivity Hazard – No

## 16. Other Information

### DISCLAIMER:

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (28 CFR1910.1200). The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. TRAXX Corporation MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the TRAXX product is fit for a particular purpose and suitable for user's method of use or application.

09022021